

# LoRaWAN Process Pressure Sensor



Smart Agriculture, Smart Building, Smart City, Smart Energy, Smart Facility, Smart Factory, Smart Farm, Smart Retail, Smart Utilities

SKU: WSLRW-PPS

## LoRaWAN PROCESS PRESSURE SENSOR WSLRW-PPS



WSLRW-PPS-H1.PNG



The WSLRW-PPS is a LoRaWAN-based process pressure sensor designed for industrial use. It supports multiple measurement types: Gage, Absolute, and Sealed Gage, with a pressure range from -1 to 1000 bar. The sensor delivers high accuracy and long-term stability.

Thanks to its ultra-low-power design and smart firmware, it can operate for up to 10 years using just two AA batteries (depending on settings). It wirelessly transmits data over distances of several kilometers to any LoRaWAN gateway, regardless of brand.

### Applications

Water Pressure Pipeline Monitor, Process Monitoring, Smart Irrigation, Fuel Monitoring, Level Monitoring, Safety Monitoring

### Notes For Applications

**Sensor Materials Compatibility:** Choose materials that won't react with the substances or degrade in corrosive media. **Environmental Conditions:** Consider the system environment (pipes, vibrations, temperature, etc.). **Pressure Range:** Choose sensors that function well within the process range. **Precision and Sensitivity:** Determine the required level of precision and sensitivity.

- ✓ **LoRaWAN communication**  
LoRaWAN communication standard to allow sensor connect to any LoRaWAN Gateway on the market.
- ✓ **10-Year battery**  
Ultra-low power sensing technology from Daviteq with Ultra-low power wireless technology allow the sensor can last up to 10 years with a 2 x AA Type battery.
- ✓ **High Accuracy & Stable**  
Advanced Piezo technology to deliver high accuracy and stable measurement
- ✓ **IP68**  
For both indoor and outdoor applications



WSLRW-PPS-H3.PNG

## DAVITEQ TECHNOLOGIES INC

Ho Chi Minh City, VN | Koblenz, DE | Melbourne, AU | Zurich, CH

+84.28.6268.2523 / 6268.2524

info@daviteq.com

www.iot.daviteq.com

Created date: Dec-21-2022

Updated date: Nov-08-2025

## Specification

Sensor	Advanced Piezo technology
Measurement range	Select from -1~1000 bar Gage/ Absolute/ Sealed Gage
Over pressure protection	1.5 x span
Accuracy & Stability	0.25% or 0.5% of span, < 0.2% span/ year
Wetted parts	304SS/316SS
Measuring Fluids	Any fluid which is workable with materials 304SS/316SS
Working temperature	-20~80°C
Compensation temperature	-10~50°C
Process connection	Standard G 1/4 or Others (consult factory)
COMMUNICATION	
SF Factors	SF7~SF12
Antenna	Internal Antenna 2.0 dbi
Battery	02 x AA size 1.5VDC, battery not included
RF Frequency and Power	860~930MHz, 14~20dBm, configurable for zones: EU868, IN865, RU864, KR920, AS923, AU915, US915
Protocol	LoRaWAN, class A
Data sending modes	Interval time and when alarm occurred
Configuration	via Downlink messages or Off-line tool (Software is free)
RF Module complies to	ETSI EN 300 220, EN 303 204 (Europe) FCC CFR47 Part15 (US), ARIB STD-T108 (Japan)
Working temperature	-40~60°C (with AA L91 Energizer®)
Dimensions	H180xW50xD40
Net-weight	250g
Housing	Polycarbonate & POM plastic, IP68

### DAVITEQ TECHNOLOGIES INC

 Ho Chi Minh City, VN | Koblenz, DE | Melbourne, AU | Zurich, CH

 +84.28.6268.2523 / 6268.2524

 info@daviteq.com

[www.iot.daviteq.com](http://www.iot.daviteq.com)

Created date: Dec-21-2022


Updated date: Nov-08-2025

PRESSURE SENSOR INSTALLED ON THE WATER PIPE




WSLRW-PPS-H2.PNG


DIMENSION DRAWING OF WIRELESS SENSOR  
Type 1 (Unit: mm)



DIMENSION DRAWING OF WIRELESS SENSOR  
Type 2 (Unit: mm)



DIMENSION DRAWING OF WIRELESS SENSOR  
Type 3 (Unit: mm)



RECOMMENDED BATTERIES

E91 AA Alkaline battery



-18 .. + 60 oC working temperature  
10-year shelf life  
3000 mAh Capacity  
Price: 1X

L91 AA Lithium battery



-40 .. + 60 oC working temperature  
20-year shelf life  
3500 mAh Capacity  
Price: 3.5X

WSLRW-PPS-H5.PNG

DAVITEQ TECHNOLOGIES INC

Ho Chi Minh City, VN | Koblenz, DE | Melbourne, AU | Zurich, CH

+84.28.6268.2523 / 6268.2524

info@daviteq.com

www.iot.daviteq.com

Created date: Dec-21-2022

Updated date: Nov-08-2025

## Ordering Information

ITEM CODE	DESCRIPTIONS
WSLRW-PPS-G10-02	LoRaWAN Process Pressure Sensor, 0-10 barg, 304SS/316L, G 1/4"
WSLRW-PPS-G20-02	LoRaWAN Process Pressure Sensor, 0-20 barg, 304SS/316L, G 1/4"
WSLRW-PPS-G40-03	LoRaWAN Process Pressure Sensor, 0-40 barg, 304SS/316L, 1/4" NPT
WSLRW-PPS-G70-03	LoRaWAN Process Pressure Sensor, 0-70 barg, 304SS/316L, 1/4" NPT
WSLRW-PPS-G100-04	LoRaWAN Process Pressure Sensor, 0-100 barg, 304SS/316L, 1/2" NPT
WSLRW-PPS-G250-04	LoRaWAN Process Pressure Sensor, 0-250 barg, 304SS/316L, 1/2" NPT
WSLRW-PPS-G400-04	LoRaWAN Process Pressure Sensor, 0-400 barg, 304SS/316L, 1/2" NPT
WSLRW-PPS-G700-04	LoRaWAN Process Pressure Sensor, 0-700 barg, 304SS/316L, 1/2" NPT
WSLRW-PPS-G1000-04	LoRaWAN Process Pressure Sensor, 0-1000 barg, 304SS/316L, 1/2" NPT

### DAVITEQ TECHNOLOGIES INC

 Ho Chi Minh City, VN | Koblenz, DE | Melbourne, AU | Zurich, CH

 +84.28.6268.2523 / 6268.2524

 info@daviteq.com

[www.iot.daviteq.com](http://www.iot.daviteq.com)

Created date: Dec-21-2022

Updated date: Nov-08-2025